



Firefly Fire Pumps Pvt. Ltd.

C-7, M.I.D.C. Gokul Shirgoan
Kolhapur - 416 234 [M. S.] INDIA.
Tel. No. : +91-231-2671527, 2672359.
Fax : +91-231-2671061.
E-MAIL ADDRESS: info@fireflypumps.com

TECHNICAL DATA SHEET FOR MFV-MP-1020

Performance Data:

- ❖ Rated Performances in Low Pressure Stage:-

Discharge (lpm)	Pressure (bar)	Power		RPM
		kilowatts	Horsepower	
2000	10	67	90	2980
2270	7	52	70	2650

- ❖ Rated Performances in High Pressure Stage:-

Discharge (lpm)	Pressure (bar)	Power		RPM
		kilowatts	Horsepower	
300	40	85	114	2950

- ❖ Suction Inlet:- 100 mm
- ❖ Priming Performance Range:- up to 8 meters
- ❖ Recommended Priming Speed:- 100 rpm to 2500 rpm
- ❖ Thermal Relief Valve Activation:- 55°C to 60°C
- ❖ Typical Dimensions:-

Length	Width	Height
730 mm	508 mm	645 mm
28.7 inches	20 inches	25.4 inches

*The Performance data stated above is observed at test conditions (3.0 meters suction lift at NTP conditions).

*For capacities other than stated above, please contact technical department.

* The right of technical modifications & improvement without prior notice is reserved.